T7P Terminal

integrated POS terminal and printer from Hypercom

T7P Features:

- Small footprint takes up less counter space
- Easy-to-learn, simple-to-use 35-key keyboard
- Fast transactions and authorizations
- Clerk-friendly operations, easily changed paper and ribbons
- Cashier-replaceable printer module
- High visibility 2 x 20 backlit LCD display
- Full Track 1 and 2 card reader standard
- Field-proven, high reliability
- Smart card reader option (T7PS), EMV-certified

The T7P is designed for upgrading authorizationonly equipment and for merchants moving to data capture and debit applications. It features an integrated modular impact or quiet thermal printer. T7P can read all types of credit, debit, check and charge cards, and an external PIN pad can be attached to support cardholder entry of PIN numbers. Dedicated function keys allow one-step operation of everyday processes.

Price/performance benefits of the T7P include savings on user training, reduced telephone line costs, and shorter processing and settlement times. The T7P also accommodates new software applications demanded by the marketplace which can be remotely downloaded from a sophisticated Terminal Management System.



T7P in a retail environment



T7P Specifications

Display	LCD Backlight	2 lines x 20 CCFL 25,000 hours to half-life		
Card reader	Magnetic stripe Reliability	Track I, 2 (Track 3 optional) 400,000 reads		
Smart card reader	IC card interface	ISO 7816, EMV-certified		
Keypad	Silicone rubber Reliability	35 keys 350,000 operations		
Comms	Modem LAN PIN pad port Peripheral compatibility	2400 bps, 1200 bps, synchronous (SDLC) and asynchronous, 9600 bps optional RS485 Hypercom LAN 2-wire or 4-wire, RS422 S7C, S7SC, S8, P7E, ICE, HFT105		
Printer	Type Columns Paper roll width Paper roll type MTBF	<u>Thermal</u> 40 2.26 in/57.5 mm, Single ply 5 million lines	<u>Impact</u> 40 2.26 in/57.7 mm I, 2, or 3-ply I.35 million lines	
Memory	RAM EPROM RAM backup	Up to 1.0 MB 32 KB 5-year battery		
Power	AC DC	85-250 V AC, 50/60 Hz 24 V, I A		
Environment	Temperature Humidity ESD	0-45 C/32-115 F Max 85%, non-condensing 12,000 volts		
Footprint	Dimensions	6.25 in x 11.5 in x 4.5 in/15.88 cm x 29.21 cm x 11.43 cm		
Weight		1.98 lbs/0.74 kg approximate weight		
Reliability	MTBF	100,000 hours (not including printer)		

WORLD HEADQUARTERS/ NORTH AMERICA	LATIN AMERICA	ASIA/PACIFIC RIM	EUROPE, MIDDLE EAST, AFRICA	
Hypercom Corporation	Hypercom Latin America	Hypercom Asia Ltd.	Hypercom Europe Ltd.	<u>HYPERCOM</u>
2851 W. Kathleen Road	Rua Joaquim Floriano 72	21/F Metro Centre II	Unit 2, Woking Eight	V V B
Phoenix, Arizona 85053 USA	16° andar Cj161 04534-000 ItaimBibi	21 Lam Hing Street Kowloon Bay	Forsyth Road Woking, GU21 5SB	www.hypercom.com
	São Paulo, Brazil	Hong Kong	United Kingdom	1.077.040.7020
TEL: +1.602.504.5000	TEL: +55.11.3365.2600	TEL: +852.2561.6800	TEL: +44.1.483.718600	
FAX: +1.602.504.4578	FAX: +55.11.3365.2610	FAX: +852.2561.5890	FAX: +44.1.483.718601	

©2001 Hypercom Corporation, all rights reserved. Hypercom, the Hypercom logo and ICE-PAC are registered trademarks of Hypercom Corporation. The Global Leader in Electronic Transaction Solutions is a trademark of Hypercom Corporation. All other products or services mentioned in this document are trademarks, service marks, registered trademarks or registered service marks of their respective owners. Hypercom Corporation (NYSE: HYC) is a leading global provider of electronic payment solutions that add value at the point-of-sale for consumers, merchants and acquirers. Hypercom products include secure card payment terminals and web appliances, networking equipment and software applications for e-commerce, mark cards and traditional payment applications. Headquartered in Phoenix, Arizona, Hypercom maintains an installed base of more than 3.5 million card payment terminals which operate in over 100 countries and conduct more than 2.5 billion transactions annually.