S9

the ideal modular upgrade








Four versions accommodate most upgrade requirements:

- · Meets all the latest security standards
- Visa-approved PIN entry
- Certified for Triple DES
- EMV4.0 type approved and compatible with Hypercom Crypto Processor (HCP)
- New easy-to-hold ergonomic design fits comfortably in customers' hands





www.hypercom.com

the ideal modular upgrade

Hand-Over Design Fights Fraud

The new Hypercom[®] S9 ensures security by letting customers always keep their credit or debit cards. Cardholders simply pick up the ergonomic S9 hand-over unit, swipe their card and enter a PIN, if needed. No need for cashier assistance.

Rock-Solid Security

ςο

The S9 incorporates the most secure criteria in electronic transaction technology globally, including new EMV standards. Easy-to-read user interface has an illuminated display and oversized, colored OK and CANCEL keys.

Reads Both Smart and Magnetic Stripe Cards

Regardless of whether customers use magnetic stripe or smart card technology, three models of the cost-effective S9 accommodate both technologies and card readers are co-located to avoid user confusion. Model S9 is a PIN pad only. Model S9C is a PIN pad/terminal reading magnetic stripe cards. Model S9S is a PIN pad/terminal reading smart cards. Model S9SC is a PIN pad/terminal reading both smart and magnetic stripe cards. The smart card reader on all models accepts 3V and 5V cards or economic 3V-only cards.

Fully Compatible

The S9 features Hypercom plug-and-play software and replaces all Hypercom PIN pads including the S1, S7 and S8 families. As a PIN pad, the S9 is fully compatible with all Hypercom terminals from the T7 series through the ICE[™] family. It is Triple DES certified and EMV4.0 Type approved. Also Visa approved.

World Headquarters/ North America Hypercom Corporation 2851 W. Kathleen Road Phoenix, Arizona 85053 USA

Tel: +1.602.504.5000 Fax: +1.602.866.5380 Latin America Hypercom Industria e Comercio LTDA Centro Empresarial Atibaia Rodovia Dom Pedro I, KM 87, 5 Av. Tegula, 888-Ponte Alta Atibaia 12940-000, Brazil Tel: +55.11.4417.7060 Asia/Pacific Rim Hypercom Asia Ltd. 21/F Metro Centre II 21 Lam Hing Street Kowloon Bay, Kowloon Hong Kong Tel: +85.2,2561.6800 Fax: +85.2,2561.5890

Europe/Middle East/Africa Hypercom EMEA, Inc. Unit 2, Woking Eight Forsyth Road Woking, GU21 5SB, United Kingdom Tel: +44.1483.718600 Fax: +44.1483.718601

©2003-2004 Hypercom Corporation, all rights reserved. Hypercom and the Hypercom logo are registered trademarks of Hypercom Corporation. All other products or services mentioned in this document are trademarks, service marks, registered trademarks or registered service marks of their respective owners.

Celebrating 26 years of technology excellence, involution and leadership. Hypercom Corporation is a leading global provider of electronic payment solution that add value at the point-of-transaction for consumers, merchants and acquirers, and yield increased protitability for its customers.

Widely recognized as the global payment technology innovator, Hypercom delivers comprehensive card payment terminal, network and server solutions that help merchants and financial institutions generate revenues and increase profits.

Headquartered in Phoenix, Arizona, Hypercom's card payment terminal, network and server solutions are leading the transformation of electronic payments in more than 100 countries.

Specifications:

Display LCD: 2 x 16 characters Backlight: 25,000 hours (calculated)

Keypad Membrane: 16 silicone rubber keys

Card Reader

Magnetic Stripe Reader (optional): Tracks 1, 2 (standard) Tracks 2, 3 (optional) 400,000 reads (calculated) Smart Card Reader (optional): EMV4.0 certified; ISO 7816; non-captive; 3V and 5V cards; two 5V SAMS

Communications

PIN Pad Port: RS-422 PIN (standard), RS-232 3-wire (optional)

Power 12 V, 100m A (standard)

Security Physical: Visa PED approved; Intrusion detection, encryption coprocessor

PIN Encryption

DES: Visa PED appoved;PIN-ANSI 9.8, MAC-ANSI 9.9, PART 1-ANSI 9.24, Triple DES Key Management: Master/session keys (12) or DUKPT

Footprint

Dimensions: 3.54" x 6.73" x 2.09"/ 90mm x 171mm x 53mm

Weight 0.29lbs/130g (approximate)

Environment

Temperature: 0-45°C/32- 115°F Humidity: Max 85%, non-condensing ESD: 12,000 volts

Reliability 100,000 hours (MTBF calculated)

Configuration Options Option 1: PIN pad only

Option 2: PIN pad w/magnetic stripe reader Option 3: PIN pad w/magnetic stripe and smart card reader

Specifications subject to change without notice.

940414-001, Rev. D



05/04

innovation. results. leadership.

www.hypercom.com